

Display Panel

CT-MP08 Caller location unit



The CT-MP08 caller display panel features a large, clear, wide viewing angle display with volume control, standby battery and fitted on a swivel bracket. The optional paging facility allows staff to receive alpha-numeric calls wherever they are on site.

SPECIFICATION

Display

- Surface mount LED array - wide viewing angle
- 56mm red characters – displaying call type and room / bed number
- Waiting calls scroll on display
- 16 live calls held in memory and scrolled on display
- Highest level given priority
- Mains power failure indicator
- Remote accept

Sounder

- Distinctive alarm tones for Call, Assistance & Emergency
- Rotary volume control

Active Call Upgrade

- If call remains unanswered, call incremented to next level – variable time settings for each individual call point (set by call point)

Maintenance

- Low battery indicator for individual call points
- Indication if a call point is not working
- Lead fault indication for individual call points
- Diagnostic reporting

Mimic Displays

- Radio mimic display panels can be added to the system to provide call indication throughout the building

Paging

- Panels can be linked to radio paging systems to provide alpha-numeric messages

Numerical Range

- 001 – 999 to cater for house, ward or floor numbering systems

Display size

- (W) 275mm x (H) 105mm x (D) 55mm

Standards

- Meets EMC directive
- Meets low voltage directive
- RA type approved
- CEPT/ERC
- RoHS/WEEE compliant

GD Systems
22 Teignbridge Business Centre
Cavalier Road
Heathfield
Newton Abbot
TQ12 6TZ

t: 01626 818217 | e: sales@gdsystems.com | w: gdsystems.com